



MATERIAL	PALLETS (4-way entry)	CERTIFICATIONS	CAPACITY	DIMENSIONS	DYNAMIC LOAD
<p>Inner container</p> <ul style="list-style-type: none"> ■ extrusion blow-moulded HDPE ■ SMP protective barrier (also available) ■ UV protection (also available) <p>Outer jacket</p> <ul style="list-style-type: none"> ■ welded tubular steel grid ■ galvanised <p>Bottom plate</p> <ul style="list-style-type: none"> ■ made of steel plate to provide stability and to facilitate minimum residual contents ■ specially reinforced 	 <p>composite MX-C</p> <p>steel frame MX-S</p> <p>steel runner</p> <p>plastic frame MX-P</p> <p>plastic runner</p> <p>full-plastic frame MX-FP</p> <p>full-plastic runner</p>	<p>UN 31 HA1/Y (also available)</p> <ul style="list-style-type: none"> ■ maximum density 1.9 <p>FDA (also available)</p> <ul style="list-style-type: none"> ■ safe for food products 	<p>MX 640 640 litre (170 gal)</p> <p>MX 820 820 litre (220 gal)</p> <p>MX 1000 1000 litre (275 gal)</p> <p>MX 1250 1250 litre (330 gal)</p>	<p>MX 640 1200 x 800 x 1000 (L x W x H)</p> <p>MX 820 1200 x 1000 x 1000 (L x W x H)</p> <p>MX 1000 1200 x 1000 x 1160 (L x W x H)</p> <p>MX 1250 1250 x 1000 x 1350 (L x W x H)</p>	<p>Filled ECOBULK according to the specific weight of the filling goods</p>  <p>up to 1.5 2-high</p> <p>more than 1.5 1-high</p>
		FILLING OPENING	OUTLET VALVES	WEIGHT	STATIC LOAD
		<ul style="list-style-type: none"> ■ DN 150 with screw cap ■ DN 225 with screw cap ■ DN 400 with clamp-ring lid 	<ul style="list-style-type: none"> ■ integrated butterfly valve DN 50 ■ screwable butterfly valve DN 50 or DN 80 DN 150 also available ■ screwable ball valve DN 50 	<p>MX 640 47 kg (MX-S), 51 kg (MX-P)</p> <p>MX 820 58 kg (MX-C), 55 kg (MX-S), 57 kg (MX-P)</p> <p>MX 1000 63 kg (MX-C), 60 kg (MX-S), 62 kg (MX-P), 64 kg (MX-FP)</p> <p>MX 1250 70 kg (MX-C), 67 kg (MX-S), 69 kg (MX-P)</p>	<p>max. 4-high</p> 