



## II.IV ECODRUM S-DS1 Open-head drums

**SCHÜTZ**  
INDUSTRIAL PACKAGING  
The Future's Technology. Today.



### TECHNICAL DATA

<b>Drum Type</b>	S-DS1 30 l
<b>Nominal Capacity</b>	30 l
<b>External Height</b>	520 mm
<b>External Diameter</b>	315 mm
<b>Compression Resist.</b>	8,500 N
<b>Total Weight</b>	2,1 kg
<b>UN Certification</b>	UN 1H2/X60/S/



## II.IV ECODRUM S-DS1 Open-head drums

**SCHÜTZ**  
INDUSTRIAL PACKAGING  
The Future's Technology. Today.



TECHNICAL DATA	
Drum Type	S-DS1 60 l
Nominal Capacity	60 l
External Height	620 mm
External Diameter	400 mm
Compression Resist.	10,000 n
Total Weight	3,5 kg
UN Certification	UN 1H2/X105/S/



## II.IV ECODRUM S-DS1 Open-head drums

**SCHÜTZ**  
INDUSTRIAL PACKAGING  
The Future's Technology. Today.



TECHNICAL DATA	
Drum Type	S-DS1 120 l
Nominal Capacity	120 l
External Height	800 mm
External Diameter	496 mm
Compression Resist.	18,000 N
Total Weight	6,0 kg
UN Certification	UN 1H2/X225/S/



## II.IV ECODRUM S-DS1 Open-head drums

**SCHÜTZ**  
INDUSTRIAL PACKAGING  
The Future's Technology. Today.



TECHNICAL DATA	
<b>Drum Type</b>	S-DS1 120 l** with tight-head lid
<b>Nominal Capacity</b>	120 l
<b>External Height</b>	800 mm
<b>External Diameter</b>	496 mm
<b>Compression Resist.</b>	18,000 N
<b>Total Weight</b>	7,0 kg
<b>UN Certification</b>	UN 1H2/Y1.5/100/

\*\* for liquid goods



## II.IV ECODRUM S-DS1 Open-head drums

**SCHÜTZ**  
INDUSTRIAL PACKAGING  
The Future's Technology. Today.



TECHNICAL DATA	
Drum Type	S-DS1 150 l
Nominal Capacity	150 l
External Height	965 mm
External Diameter	503 mm
Compression Resist.	18,000 N
Total Weight	6,7 kg
UN Certification	UN 1H2/X232/S/



## II.IV ECODRUM S-DS1 Open-head drums

**SCHÜTZ**  
INDUSTRIAL PACKAGING  
The Future's Technology. Today.



TECHNICAL DATA	
Drum Type	S-DS1 216,5 l
Nominal Capacity	216,5 l
External Height	945 mm
External Diameter	585 mm
Compression Resist.	18,000 N
Total Weight	9,6 kg
UN Certification	UN 1H2/X320/S/